

G12R-66P

N-type Bifacial Double Glass Module

HSM-ND66-GR605~630

630W

Maximum Power Output

23.3%

Maximum Efficiency



Superior Customer Value

- Container space utilization saves shipping costs
- Low-voltage design optimizes BOS cost
- Optimized for diverse installation needs



High Energy Yield

- Consistent high yield in varying conditions
- Enhanced thermal resistance and bifacial power generation



Long-term Reliability

- Advanced weather-resistant encapsulation
- Aluminium alloy frame and heat strengthened glass
- Resistant to harsh environmental conditions

Comprehensive Products and System Certificates



IEC 61215 / IEC 61730 ISO 9001:2015 ISO 45001:2018 ISO 14001:2015


Linear Performance Warranty



15 Years
Product Warranty



30 Years Linear
Performance Warranty



Electrical Parameters (STC* & BNPI*)

* STC: Irradiance 1000W/m², Cell Temperature 25°C, AM1.5, Measuring Tolerance: ±2%* BNPI: Back Irradiance 135W/m², Cell temperature 25°C, Atmospheric quality AM 1.5G, Wind speed 1m/s

Testing Condition		STC	BNPI	STC	BNPI	STC	BNPI	STC	BNPI	STC	BNPI	STC	BNPI
Maximum Power	P _{max} (W)	605	668	610	674	615	679	620	685	625	690	630	696
Open Circuit Voltage	V _{oc} (V)	48.28	48.43	48.50	48.66	48.72	48.86	48.94	49.11	49.16	49.30	49.38	49.50
Short Circuit Current	I _{sc} (A)	15.90	17.55	15.95	17.61	16.00	17.66	16.05	17.73	16.10	17.77	16.15	17.81
Maximum Power Voltage	V _{mp} (V)	40.39	40.39	40.59	40.61	40.79	40.79	40.98	41.00	41.18	41.20	41.37	41.40
Maximum Power Current	I _{mp} (A)	14.98	16.54	15.03	16.60	15.08	16.65	15.13	16.71	15.18	16.75	15.23	16.81
Module Efficiency	(%)	22.4		22.6		22.8		23.0		23.1		23.3	

Electrical Characteristics with Different Bifacial Gain*

* The additional gain from the back side depends on mounting (structure, height, tilt angle etc.) and albedo of the ground.

Bifacial Gain		5%	10%	5%	10%	5%	10%	5%	10%	5%	10%	5%	10%
Maximum Power	P _{max} (W)	635	666	641	671	646	677	651	682	656	688	662	693
Open Circuit Voltage	V _{oc} (V)	48.28	48.28	48.50	48.50	48.72	48.72	48.94	48.94	49.16	49.16	49.38	49.38
Short Circuit Current	I _{sc} (A)	16.70	17.49	16.75	17.55	16.80	17.60	16.85	17.66	16.91	17.71	16.96	17.77
Maximum Power Voltage	V _{mp} (V)	40.39	40.39	40.59	40.59	40.79	40.79	40.98	40.98	41.18	41.18	41.37	41.37
Maximum Power Current	I _{mp} (A)	15.73	16.48	15.78	16.53	15.83	16.59	15.89	16.64	15.94	16.70	15.99	16.75

Temperature Coefficient


* NMOT: Irradiance 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s

Nominal Module Operating Temperature*	43±2°C
Temperature Coefficient of I _{sc}	+0.045%/°C
Temperature Coefficient of V _{oc}	-0.24%/°C
Temperature Coefficient of P _{max}	-0.28%/°C

Operating Parameters

Operating Temperature	-40~+85°C
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	30A
Power Bifaciality	80±5%

Curve Graph



Engineering Drawing

[Unit: mm]

Mechanical Data

* Please refer to installation manual for details

No. of Cells	132pcs (6×22)
Dimension	2382×1134×30mm
Weight	32.6kg±3%
Front Glass	2.0mm, Heat Strengthened, AR coating Glass
Back Glass	2.0mm, Heat Strengthened Glass
Frame	Anodized Aluminium Alloy
J-Box	IP68, three diodes
Cables	4.0mm ² , +300mm, -200mm (can be customized)
Maximum Static Load	Front: 5400Pa/Back: 2400Pa*
Fire Rating	IEC Class C

Packaging Configuration

Modules per Pallet	36pcs
Modules per 40'HQ Container	720pcs
Pallets per 40'HQ Container	20pcs

