

H48074

High voltage lithium battery

H48074 - 3.55 kWh Modules

Pylontech's H48074 lithium batteries represents the latest technological frontier for high voltage photovoltaic storage applications.

LiFePO4 battery technology also has the following **benefits**:

- **Longer Life cycle**, which exceeds 5000 cycles, corresponding to about 11 years of work, with an end-of-life capacity of 80%;
- The internal **molecular structure** of LiFePO4 batteries is **more stable** and **safer**;
- Depth of discharge up to 90%;
- **Easy expansion** to increase the power of storage;
- A **Compact and modular design** for easy installation / upgrade;
- Ability to operate under different temperature conditions;
- **Advanced BMS** that allows you to report alarm in real time.

Dimensions:

Width: 442 mm
Height: 132 mm
Depth: 390 mm
Weight: 32 kg



SAVE YOUR PLANET
www.energysynt.com

Technical data

Lithium Battery

Model	H48074
ELECTRICAL DATA	
Cell technology	Li-ion (LFP)
Nominal voltage [V] (single module)	48
Nominal capacity [kWh/Ah] (single module)	3.552 / 74
Depth of discharge DOD [%]	95
Current [A]	37 (nominal) - 74 (max)
Charge voltage [V, min.~max.]	43.5 ~ 54
BUS	
Communication Bus	RS485, CAN
Communication protocol	YD/T 1363.3-2005
DIMENSIONS AND WEIGHT	
Width [mm]	442
Height [mm]	132
Depth [mm]	390
Weight [kg]	32
GENERAL DATA	
Charge/ discharge operation temperature [°C]	0 ~ 50
Storage Temperature [°C]	-20 ~ 60
Protection Class	IP20
Operation Life at 25 °C	15+ years
Life Cycles	5000
Backup time [Nominal power 500 W]	≥ 5 h
Duration of charge maintenance	6 Months with off battery
Transfer certificate	TÜV, CE, UN38.3, UN 3090
EMC	IEC 61000, EN 55022, GR-1089, GB/T 2423

Energy S.p.A.

Registered office:
Piazza Manifattura, 1
38068, Rovereto TN
Tel. +39 0464 350812 - Fax +39 0464 350512



www.energysynt.com
www.retiintelligenti.com

Energy S.p.A.

Operations/Warehouse:
Via Zona Industriale, 10 - 35020
Sant'Angelo di Piove di Sacco (PD) - Italy
info@energysynt.com
Tel. +39 049 2701296 - Fax +39 049 8599098